



404 / 708 / 715 Series 230/240V nominal input single phase models

Meters	Model		
N/A	404-EB	-	715-EB
Analogue: Volts & Current	404-EA	708-EA	715-EA
Digital: Volts & Current	404-ED	-	715-ED
Rated current	4 Amps	8 Amps	15 Amps
Output voltage	0 - 115% of input voltage		
No-load loss	12W	15W	30W
Approx weight	8kg	12Kg	15kg
Number of turns on winding	380	383	258

FEATURES

- Enhanced Safety
-
- Thermal Cut-out
-
- Portable
-
- Robust Construction
-
- Bench or wall mounting
-
- Output connections via IEC320
-
- Gold plated contact area
-
- No waveform distortion
-
- No harmonic generation
-
- High efficiency
-
- Continuously variable 0 - 115%
-
- Designed and manufactured in the UK
-
- CE Marked
-
- Safety to EN61010
-

Regavolt®
Variable Transformers

SPECIFICATION

Input Voltage	180 to 240V single phase
Input frequency	47-65Hz
Input indication	Power ON lamp
Input connection	IEC320 socket
Output voltage	0 - 115% of input
Output connection	IEC320 socket
Analogue metering	+/- 5% fsd (voltage calibrated at 240V +/- 2.5%)+/-
Digital metering	+/- 3% sinusoidal waveforms
Protection	Three pole thermal circuit breaker
Ambient	0°C to +40°C
Humidity	0 - 95% non condensing
Dimensions (mm)	300(h) x 212(w) x 200(d)
Standard accessories	2 Meter input mains lead and IEC320 output socket

Note: 404 (4 Amp) and 708 (8 Amp) series models are fitted with BS1363/A UK 3 pin 13 Amp plug.
715 series rated at 15 Amps is fitted with BS4343 industrial 2P+E plug

OPTIONAL ACCESSORIES

IEC socket to Safe Block



IEC socket to 4 way UK socket

