



## 404 / 708 / 715 Series 230/240V nominal input single phase models

Meters	Model		
N/A	404-EB	-	715-EB
Analogue: Volts & Current	404-EA	708-EA	715-EA
Digital: Volts & Current	404-ED	-	715-ED
Rated current	4 Amps	8 Amps	15 Amps
Output voltage	0 - 115% of input voltage		
No-load loss	12W	15W	30W
Approx weight	8kg	12Kg	15kg
Number of turns on winding	380	383	258

### FEATURES

- Enhanced Safety
- 
- Thermal Cut-out
- 
- Portable
- 
- Robust Construction
- 
- Bench or wall mounting
- 
- Output connections via IEC320
- 
- Gold plated contact area
- 
- No waveform distortion
- 
- No harmonic generation
- 
- High efficiency
- 
- Continuously variable 0 - 115%
- 
- Designed and manufactured in the UK
- 
- CE Marked
- 
- Safety to EN61010
- 

### SPECIFICATION

Input Voltage	180 to 240V single phase
Input frequency	47-65Hz
Input indication	Power ON lamp
Input connection	IEC320 socket
Output voltage	0 - 115% of input
Output connection	IEC320 socket
Analogue metering	+/- 5% fsd (voltage calibrated at 240V +/- 2.5%)
Digital metering	+/- 1% sinusoidal waveforms
Protection	Three pole thermal circuit breaker
Ambient	0°C to +40°C
Humidity	0 - 95% non condensing
Dimensions (mm)	300(h) x 212(w) x 200(d)
Standard accessories	2 Meter input mains lead and IEC320 output socket

Note: 404 (4 Amp) and 708 (8 Amp) series models are fitted with BS1363/A UK 3 pin 13 Amp plug.  
715 series rated at 15 Amps is fitted with BS4343 industrial 2P+E plug

### OPTIONAL ACCESSORIES

IEC socket to Safe Block



IEC socket to 4 way UK socket



**Regavolt**<sup>®</sup>  
Variable Transformers